



Recommended PCB Layout

TOP-LINK

Notes:

Material(材质):
Housing: PA46, UL94 V-0 Color Black.
Contact: Brass
Spring : Stainless steel wire

2 Plating:

1)Body: Min 0.1um Gold plating over min. 1.4um Nickel plating (Body: 镀金0.1um Min 镍底1.4um Min)
2)Plunger: Min 0.25um Gold plating over min. 2.5um Nickel plating (Plunger: 镀金0.25um Min 镍底2.5um Min)

3 Mechanical:

Force(力): 70±20 gf at 0.65 mm stroke
Total stroke(总行程): 1.00mm
Durability(寿命): 10,000 cycle min

4 Electrical(电性能)

Contact resistance(接触阻抗): 50mOhm Max.
Voltage rating(额定电压): 36V DC Max
Current rating(额定电流): 2.0A

LDC	-
DIST	-

LTR	REVISION	APVD	DATE
	update tolerance		2007/12/20
	RECORD		

DIMENSIONS IN MM	
TOLERANCES UNLESS OTHER SPECIFIED	
0	= ±
0.0	= ±0.15
0.00	= ±0.10
0.000	= ±
ANGLE: ±1°	
SURF TEXTURE: 3.2/	
REMOVE BURRS, BREAK SHARP EDGES R0.05 MAX	
DD NOT SCALE PRINT	

MATL	HT TR	FIN
1	-	-
DWN	APVD	
Qln	REL	
CHK		
NAME: PGGD CONNECTOR 6 POSITIONS		
PGC-1.26-3.6-2R-6P-1.5PH		
SCALE	DWG NO.	SHEET
1:1	A4 C-100191	1 OF 1
		REV E

100191-6	PART NUMBER

USED DN

-