



TOP-LINK

Notes:

Material(材质):

Housing: High temp. Plastic, UL94 V-0 Color Black.

Contact: Brass

Spring : Stainless steel wire

2 Plating:

1)Body: Min 0.1um Gold plating over min. 1.4um Nickel plating

(Body: 镀金0.1um Min 镀底1.4um Min)

2)Plunger: Min 0.4um Gold plating over min. 1.4um Nickel plating

(Plunger: 镀金0.4um Min 镀底1.4um Min)

Mechanical:

Total stroke(总行程): 1.30mm

Force(弹力): 125±35gf per pin at 1.0mm stroke

Durability(寿命): 10,000 cycle min.

Electrical(电性能)

Contact resistance(接触阻抗): 30mOhm Max.

Voltage rating(额定电压): 36V DC Max

Current rating(额定电流): 2.0A

| | |
|------|---|
| LDC | - |
| DIST | - |

4

3

2

1

| | | |
|-----------------|------|-----------|
| NEW | APVD | DATE |
| REVISION RECORD | | 809/11/09 |
| LTR | | |

DIMENSIONS IN MM
TOLERANCES UNLESS OTHER SPECIFIED

0 = ±
0.0 = ±0.15
0.00 = ±0.10
0.000 = ±

ANGLE: ±1°

SURF. TEXTURE: 32/

REMOVE BURRS, BREAK SHARP EDGES R0.05 MAX DD NOT SCALE PRINT

| | | |
|-------|----------------------------|----------|
| MATL | HT TR | FIN |
| DWN | APVD | |
| CHK | REL | |
| NAME | PGGD CONNECTOR 6 POSITIONS | |
| SCALE | DWG NO. | C-110658 |
| 1:1 | A4 | |
| | ND. | |
| | PGC-1.5-6.5-2R-6P-2.54PH | |
| | SHEET 1 OF 1 | |
| | REV A | |

| |
|-------------|
| 110658-6 |
| PART NUMBER |

USED DN

-

A

B

C

D