



Table 1 Mechanical performance		
Working height	8.50mm	120gf Min<2.1>
Durability	10000cycle	

## Recommended Page Layout

- Notes:
- 1 Dimensions shall be interpreted per ASME Y14.5M.
  - 2 Mechanical performance(See the table 1 <2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
  - 3 Electrical performance  
Resistance: 30mOhm Max.  
Current rating: 2.0A
  - 4 RoHS compliant.

Top-Link Electronics Ltd	Type	Customer drawing	Unit	mm	Weight
TOLERANCES UNLESS OTHER SPECIFIED	DWN:	APVD:	<div style="display: flex; justify-content: space-between; align-items: center;"> <div> <i>Top-Link</i>  <b>Electronics</b> </div> <div> Top-Link  Electronics Ltd </div> </div>		
0.0 = ± 0.15 0.00 = ± 0.10 0.000 = ± 0.05	Qin Zuo Zhong	REL:			
Angle: ±1 SURF. TEXTURE: REMOVE BURRS. BREAK SHARP EDGES R0.05 MAX. DO NOT SCALE PRINT.	Name	Customer drawing			
Scale	Size	DWG No.	Page	Rev.	
1:1	A4	C-100893	1/1	1	